


## Magnetic sheet separator



Product	
HSS	Magnetic Sheet separator
HSSZ	Special magnetic Sheet separator

Magnet quality	
F	GSFD-33, Br 4100 gauss, Tmax 225°C
N	N35, Br 11 200 gauss, Tmax 80°C /
	N38, Br 12 600 gauss, Tmax 80°C /
	N45, Br 13 700 gauss, Tmax 80°C
HT	N35SH, Br 12 200 gauss, Tmax 150°C
ET	N35EH, Br 12 200 gauss, Tmax 200°C
ST	Sam-cobalt GSS-28, Br 11 000 gauss, Tmax 350°C
ES	N52, Br 14 800 gauss, Tmax 80°C

Type	
BA	Basic (permanent magnetic)
PF	Switchable - Pneumatic operated – Flat front
PA	Switchable - Pneumatic operated – Arched front
MS	Switchable - Manually operated
RD	Rod type (permanent magnetic)
ZZ	Special type

**Width x height (thickness) [mm]** (for type BA/PF/PA/MS)

**D (Diameter) [mm]** (for type RD)

For type BA:		
Type:	Ferrite	Neodymium
0	73x29	43x22
1	n/a	73x22
2	114x47	114x22
3	154x47	n/a
4	204x92	n/a
5	304x97	n/a

**Length [mm]**

Options	
B	Basic
C	Connection for air nozzles
S	Incl. Sensors for on/off detection
Z	Special type